

## Betek Parquet Glue

### Product Description:

67% solid polyvinyl acetate emulsion with filler that is stabilized with polyvinyl alcohol and surfactant.

### Application Areas:

Developed specifically for affixing parquets to concrete floor. Enables odorless work since it does not contain any solvents.

### Technical Specifications:

|                              |               |
|------------------------------|---------------|
| Appearance                   | Pink          |
| Solid Ratio (%)*             | 67 ± 2        |
| pH                           | 7,0 ± 1,0     |
| Viscosity (mPa.s)**          | 40000 ± 10000 |
| Density (g/cm <sup>3</sup> ) | 1.37 ± 0.02   |
| MFFT                         | 10 ± 1        |

\*3 hours in 110°C-115°C

\*\*Brookfield LVDV-II +, 20°C, Spindle 3/20 rpm

### Surface Preparation:

- Clean all types of dust, oil and dirt on the application surface.
- Ensure the surface temperature and the ambient temperature are above +10°C during application.
- Apply the glue in an amount that overflows from the edges of the application surface and wipe the overflowing product with a damp cloth.
- Fix after waiting maximum 10 minutes.
- The product is ready-to-use. Do not add any water.
- Close the lid of the package firmly after the application.
- Apply the glue to the surface with toothed trowel.
- After application, all used tools should be cleaned with water.
- Avoid using any rusty tool.

### Dry Time:

Varies between 0.5 to 2 hours depending on the thickness of the applied film, the type of the application surface, the temperature and the humidity of the environment.

### Consumption:

1-1.5 kg/m<sup>2</sup> depending on the thickness of the applied film and the application surface.

### Storage:

Can be stored for 1 year provided that its package is unopened and it is in a 0-40°C place away from sunlight.

